



# ME 010-508 Open ends header



Pitch: 5.08mm(0.200inch)





## SPECIFICATIONS

			CUL	VDE
負載電壓	Rated Voltage	Bemessungsspannung	AC 300V	AC 400V
負載電流	Rated Current	Bemessungsstrom	16A	16A
塑膠本體	Housing Material	Isolierstofftyp	Polyamide66(UL94V-0)	
焊針	Solder Pin	Lötstift	□1.0mm, Brass, Tin plated	
操作溫度	Operating Temperature	Umgebungstemperatur	-40°C to + 105°C	
PC板孔徑	PCB Hole Diameter	Lochdurchmesser	φ1.5mm	
UL File No.	E167040			

TABLE

Item No.	A(mm)	A(inch)
ME010-50802	10.2	0.400
ME010-50803	15.2	0.600
ME010-50804	20.3	0.800
ME010-50805	25.4	1.000
ME010-50806	30.5	1.200
ME010-50807	35.6	1.400
ME010-50808	40.6	1.600
ME010-50809	45.7	1.800
ME010-50810	50.8	2.000
ME010-50811	55.9	2.200
ME010-50812	61.0	2.400
ME010-50813	66.0	2.600
ME010-50814	71.1	2.800
ME010-50815	76.2	3.000
ME010-50816	81.3	3.200
ME010-50817	86.4	3.400
ME010-50818	91.4	3.600
ME010-50819	96.5	3.800
ME010-50820	101.6	4.000
ME010-50821	106.7	4.200
ME010-50822	111.8	4.400
ME010-50823	116.8	4.600
ME010-50824	121.9	4.800



PCB Layout

