



**NORDIC POWER**



## SPECIFICATION

ITEM	SPS-300
OUTPUT POWER	CONTINUOUS POWER 300W      SURGE POWER 900W
STANDBY CURRENT	DC 12V < 0.5A      DC 24V < 0.4A
INPUT VOLTAGE	DC12V : 10V~15V      DC24V : 20V~30V
OUTPUT VOLTAGE	AC 100V, 110V, 120V, 220V, 230V, 240V
OUTPUT WAVEFORM	Modified Sine Wave
EFFICIENCY	> 90%
※ INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V
※ OUTPUT REGULATION	+5/-8% INTELLIGENT AVR
※ OUTPUT FREQUENCY	50Hz , 55Hz , 60Hz      CRYSTAL CONTROLLED.
※ COOLING	AUTO-OPERATION FAN
※ OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION
※ LOW BATTERY	< 10.5V or 21.5V ± 0.5V/1V PRE-ALARM      < 9.5V or 20V ± 0.5V/1V SHUT DOWN & ALARM
※ OVER HEATING	> 60°C PRE-ALARM      > 65°C SHUT DOWN & ALARM
※ OVER LOAD	> 330W PRE-ALARM      > 360W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE
FUSE	DC 12V : 35A * 1PCS      DC 24V : 20A * 1PCS
AC OUTLET	2 AC OUTLETS      EUROPEAN TYPE : 1 AC OUTLET
DIMENSION (L*W*H)	120*73*73mm
NET WEIGHT	0.6Kg

※ MARK ARE OUR UNIQUE FUNCTIONS