



Saves Your Energy

PRODUCT SPECIFICATION

24.2.2015

1/2



SR1



Name: **Joint compound**
For SL, SM and KG, 225 g

Type: SR1

EAN: 6418677405402

Description: SR1 is used to prevent oxidation on aluminium surfaces. The use of the wire brush and joint compound SR1 reduces the transition resistance. It also protects the connection from corrosion. There are no skin-irritant ingredients in the grease. Used for SL, SM and KG connectors and aluminium, steel and copper conductors.

Package: 25/1350

Unit: PCS

Technical specification

Dimensions

Weight 0.225 kg

Features

For connector SLxx, SMxx, KGxx

Use: SR1 is lithium based grease which contains oxidation and corrosion preventing chemicals and is used on brushed aluminium surfaces to prevent oxidation and corrosion. Brushing and greasing lowers the contact surface resistance. Can be used indoors and outdoors and is compatible with copper connections.

Prolonged or recurring skin contact can cause dryness, irritation and infections of the skin.

Construction: Base oil viscosity cSt / 40 °C 112
Base oil viscosity cSt / 100 °C 10
Liquefaction point °C min. 180
Usable in temperature range of °C -30...+110
NLGI-class 2
Coagulant type: Lithium
SKF Emcor WWO distilled water /ISO 11007mod 0-0
Copper corrosion 24h/100°C/ASTM D4048 1b
Oil separation 168h/40 °C/IP 121 6%

Markings: SR1, Ensto



Saves Your Energy

PRODUCT SPECIFICATION

24.2.2015

2/2



SR1

Standard:

Connector grease
DIN 51502 K2K-30
ISO 6743 ISO-L-XCCHA2

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2770

www.ensto.com