

Customer : Schukat Electronic Vertriebs GmbH


Drawing No. :1010306-51816

Seite 1 / 1

created: 29/11/2012 14:30:00

Typ : A22206321036

RoHS Compliant



\varnothing D : 21 mm
 L : 36 mm
 l : 40 mm
 d : 0,8 mm

Terminals : Wire

Electrical Parameters

Rated Capacitance (C_R) @ 100 Hz / 20 °C	2200 μ F	
Tolerance	± 20 %	
Rated Voltage (U_R)	63 V	
Surge Voltage (U_S) max. 5 x 1 min / h	72 V	
Reverse Voltage (U_U) max. 1 s	2 V	
Leakage Current (I_L) @ U_R / 5 min / 20 °C	1115 μ A	
ESR typ. @ 100 Hz / 20°C	145 m Ω	
Tan δ typ. @ 100 Hz / 20°C	20 %	
Z max. @ 10 kHz / 20°C	130 m Ω	
ESL typ.	20 nH	
Rated Ripple Current (I_R) @ 100 Hz / 85°C	1,1 A	
Useful life @ I_R , U_R , 85°C	5000 h	
IEC Climatic category / Standards	40/85/56	IEC 60384-4
Applications	general industrial	
Your article No. / Project		