

ARCA 304015W



Sample photo

Order symbol: ARCA 304015W
Product nbr: 8120142
Description: Cabinet, PC
Remarks: Cover with window, 2-point locking

EAN: 6418074080134
EI. number:
 Finland: 3423219
 Electric No. 8212091980
 Denmark:
 Electric No. Sweden: 2500139

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

| Dimensions: | | Length | Width | Height | Accessories: | |
|--|--|-------------------------------|-------|--------|-----------------|---|
| mm: | | 300 | 400 | 150 | MPP ARCA 3040 | Mounting plate perforated (350x250x2 mm - 26x11 mm) |
| inch: | | 11.8 | 15.7 | 5.9 | MPMP ARCA 4030 | Mounting plate multiperforated (350x250x2 mm - □3.6 mm) |
| Materials: | | | | | MPX ARCA 4030 | Mounting plate (350x250 mm) |
| Material: | | Polycarbonate | | | DRS ARCA 304015 | DIN rail frame set |
| Base colour: | | RAL 7035 -light grey | | | IDS ARCA 3040 | Inner door set |
| Cover colour: | | RAL 7035 -light grey | | | PMK ARCA 40 | Pole mounting kit |
| Gasket material: | | Polyurethane | | | RCS ARCA 3040 | Rain canopy set |
| Temperatures: | | | | | SBK ARCA 30 | Support bar kit |
| Temperature °C (short term): | | -40 ... 120 °C | | | SBK ARCA 40 | Support bar kit |
| Temperature °C (continuous): | | -40 ... 80 °C | | | DSP ARCA HLS | Door stopper ARCA, horizontal, left, small |
| Temperature °F (short term): | | -40 ... 250 °F | | | DSP ARCA HRS | Door stopper ARCA, horizontal, right, small |
| Temperature °F (continuous): | | -40 ... 175 °F | | | | |
| Accessories: | | | | | | |
| MPS ARCA 4030 | | Mounting plate (350x250x2 mm) | | | | |
| Rating: | | | | | | |
| Ingress Protection (EN 60529): IP66 | | | | | | |
| Impact Resistance (EN 62262): IK08 | | | | | | |
| Electrical insulation: Totally insulated | | | | | | |
| Halogen free (DIN/VDE 0472, Part 815): 1 | | | | | | |
| UV resistance: UL 508 | | | | | | |
| Glow Wire Test (IEC 695-2-1) °C: 960 | | | | | | |
| Certificates: | | | | | | |
| SGS Fimko | | | | | | |
| Gost R | | | | | | |

