

Cable ties

HP-FIXIT® High-Quality-Standard cable ties

Material: polyamide 6.6 nature / black (UV resistant) acc. to **UL 94 V-2**

Temperature resistance: -40°C up to +80°C

Melting point: +250°C

Resistant against: oil, petrol, seawater, solvents, mold, diluted light organic acids and alkalis.

Width and length can be marginally different from catalogue.

free of halogen



| | |
|-----------------------|-------------------|
| Item Number | 06030 |
| Cable Ties | with UL-approval: |
| Colour | nature |
| Length [mm] | 140,00 |
| Width [mm] | 2,50 |
| max. Bundle-Ø [mm] | 35,00 |
| Tensile Strength [KP] | 8,2 |
| Tensile Strength [N] | 80,00 |

| | | |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
|  | <p>Hilpress GmbH Grützmühlenweg 40 D-22339 Hamburg Web: www.hilpress.com eMail: export@hilpress.de</p> | <p>Date: 17.04.2015</p> |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|