

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® RGB 75 – 1x0,08 mm² Special Coaxial Video cable 75 Ω



A	B	C	D
---	---	---	---

CATEGORY Coaxial cable 75 Ω (See Video Catalogue)

- A:** Soft **PVC** available in different colors. Outer cable Diam. Ø 2,80 (±0,10) mm.
- B:** Shielding O.F.C. Silver Plated copper Braid covering 95%.
- C:** Core Insulation with transparent compact PE – Diam. Ø 1,50 mm (±0,10) mm
- D:** Stranded formation in O.F.C. red copper 9x0,10 mm.
Nom. Cross section 1x0,08 mm² (75Ω).

MARKING
CUSTOM

tasker® RGB75 – 75 OHM – MINI COAX VIDEO CABLE – Made Italy
 This product is also available in **L.S.Z.H., PE, PUR**, with or without **Steel Armor**.

Cable Properties

Conductor Resistance	210 Ω/Km ± 5%
Capacity Core/Shield	67 pF/mt
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	1.500 V
Operative Temperature	-15/+70°C

Attenuation dB/100 mt.

50 MHz	19,20
100 MHz	27,90
200 MHz	40,70
400 MHz	59,20
800 MHz	85,30
1000 MHz	101,00

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. C / 13.06.16
		Outdoor Direct Burial	Esterno Interrato		X	Dynamic (Drag Chain)	Mobile in Catena			
				Dynamic (Torsion)	Mobile in Torsione		