## Meets the requirements of the energy sector

Tufvassons has a wide range of transformers and over fifty years' experience of making them ourselves. We offer transformers for environments that set high requirements on insulation and safety, the energy sector for example. We help you to make the correct choice, and if you need a product that is not available, we ensure it is made.



## Ideal for low voltage installations

The transformer is used when there are greater demands on insulation and safety than normal. It is suitable for voltage feed in SELV and PELV installations such as monitoring systems, temperature control, lighting and alarms. It goes without saying that the transformer also has short circuit and overload protection, and also complies with the insurance companies' requirement for self-extinguishing plastic in the housing.

Type: PSS 60 Part. no.: 6024-00177

Input voltage: 230V, 50-60 Hz; (N - L)

Output voltage: 24V
Rated power: 60 VA (2,5A)
Weight: 1,3 kg
Encapsulation class: IP40
Insulation class: 4.2 kV
Ambient temperature: max 40 °C

Design: Transformer in grey encapsulation made from impact resistant, self extinguishing

thermoplastics.

- Double insulated (earth connection not required).

Protected against overload and short circuit on secondary with PTC.
To reset the protecting device disconnect the mains for 10 seconds.

Primary entry knock outs 8/12mm, 2-pole 4 mm² terminal.
 Secondary entry knock outs 8/12mm, 2-pole 4 mm² terminal.

- Max torque for the terminal block is 0.25 Nm.

**Mounting:** Fast mounting on DIN-rail or wall mounting with 4 screws. **Manufacturing standard:** Security EN 61558-1; EN 61558-2-6

Emissions: EN 61 000-6-3; EN 61 000-6-4, IEC 62041 Immunity: EN 61 000-6-1; EN 61 000-6-2, IEC 62041

Other information: If required for the installation in question, the transformer must be connected by an all-pole

switch in permanent installations.







## Wiring diagram and product illustration











