



## Data Sheet | Item Number: 221-2503

Mounting carrier with strain relief; 3-way; for inline splicing connector with lever; for screw mounting; gray

<https://www.wago.com/221-2503>



Color:  gray

### Physical data

Width	29.8 mm / 1.173 inches
Height from the surface	6.5 mm / 0.256 inches
Depth	100 mm / 3.937 inches

### Material Data

Note (material data)

[Information on material specifications can be found here](#)

Color	gray
Fire load	0 MJ
Weight	5.9 g

### Commercial data

ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	25 (5) pcs
Packaging type	Box
Country of origin	CN
GTIN	4066966119848
Customs tariff number	39269097900

**Downloads**

**Environmental Product Compliance**

Compliance Search		
Environmental Product Compliance 221-2503		↓

**Documentation**

Additional Information		
Technical Section	pdf 2142.18 KB	↓

**CAD/CAE-Data**

CAD data		
2D/3D Models 221-2503		↓

CAE data		
EPLAN Data Portal 221-2503		↓

ZUKEN Portal 221-2503		↓
-----------------------	--	---

**1 Compatible Products**

**1.1 Optional Accessories**

**1.1.1 Installation**

**1.1.1.1 Mounting accessories**



**Item No.: 209-119**  
Fixing screw; for 209-120 mounting carrier



**Item No.: 209-123**  
Mounting foot with screw; can be screwed on terminal blocks with fixing flange; 6.4 mm wide; gray



**Item No.: 209-120**  
Mounting foot; can be snapped on terminal blocks with snap-in mounting foot; for mounting on relay-modules; 6.4 mm wide; gray

**1.1.2 Marking**

**1.1.2.1 Marking strip**



**Item No.: 210-834**  
Marking strips; on reel; 5 mm wide; plain; Self-adhesive; white

## Installation Notes

### Installation



Place the inline splicing connector on the carrier in front of the mounting position.



Push the connector to the center position until it snaps into place.



Mounting carrier without strain relief – snapped onto DIN-rail



Various combinations of 1- to 5-connector mounting carriers are possible via side-by-side latching mechanism.

### Strain relief



3-pole mounting carrier with strain relief