


PIN OUT



Nr./No.	Länge/Length
93371	0.25m
93568	0.50m
93569	1m
93651	10m
95567	1.5m
93570	2m
93571	3m
93572	5m
93650	7.5m

- CAT 6 Netzwerkkabel
- 2xRJ45 Stecker; PIMF doppelt geschirmt S/FTP
- Paarfolge nach EIA/TIA 568
- IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T
- angespritzte Knickschutztülle mit Längenangabe
- 4x2xAWG 27/7 CCA
- vergoldete Kontakte 8P8C
- CAT 6 (250 MHz)
- Isolierung: PVC
- RoHS-konform

- CAT 6 Network cable
- 2xRJ45 plugs; PIMF double shielded S/FTP
- pair-sequence according to EIA/TIA 568
- IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T
- molded strain relief with length specification
- 4x2xAWG 27/7 CCA
- gold plated contacts 8P8C
- CAT 6 (250 MHz)
- isolation: PVC
- RoHS compliant

Änderungen

Datum	Name	gez.:	Datum	Name
		gef.:	23.07.2013	tf
		gepr.:	23.07.2013	tf
		Norm:		
Änderungen vorbehalten / Subject to change				

Bezeichnung
**CAT 6 LC SSTP
 PIMF GRAU**
 Zeichnungs-Nr.:



Blatt
 von